CGR B2-700

80 PLUS Bronze

Type	700 Watt ATX 12V v2.3 Standard PS/2 Netzteil
PFC	Active
Connectors	- 1 x 24 Pin Mainboard - 1 x 8 (4+4) Pin EPS 12V - 2 x 4 Pin P-ATA - 6 x 15 Pin S-ATA - 1 x 4 Pin FDD - 2 x 6 Pin PCIe - 2 x 8 (6+2) Pin PCIe -
80PLUS Level	Bronze
Efficiency	>87% at 50% Load
Safety functions	Overvoltage protection (OVP) Overload protection (OLP/OPP) Short-circuit protection (SCP)
PSU fan	120mm sleeve bearing, Load-/Temperature controlled
MTBF (at 25°C)	100.000 Hours
Dimensions (W/H/D)	150mm/86mm/140mm
Guidelines	ErP/EuP (2009/125/EC); RoHs 2002/95/EG Energy Star 5.0, REACH
Extras	Sleeved cable

*More technical details are available on request.

Output characteristics						
Output	+3.3 V	+5 V	+12 V1	+12 V2	-12 V	+5 VSB
Max. Load	24 A	20 A	30 A	30 A	0.3 A	2.5 A
Max. Combined Power	150 W		648 W			
Total Power 700W						

Input characteristics
AC 100-240Vac, 50-60Hz, 10A